

DECORATIVE STAINLESS STEEL

Technical Data Sheet

Created on: 10-01-2020



© Luceco plc

Address:

Luceco plc,
Caparo House,
103 Baker Street,
London, W1U 6LN.

Telephone:

+44 (0)1952 238 100

Email Address:

info@luceco.com

Integrated LED

- Decorative LED wall light with robust stainless steel housing
- Fixed and adjustable options including PIR
- Perfect for external domestic applications including patios, walkways and entrances

Overview

Code	Type	Lumens	Power(W)
LEXDSS5UD30	Fixed Up Down	500	8
LEXDSS5UD30P	PIR Fixed Up/Down	500	8
LEXDSS3F30	Fixed Down	300	4
LEXDSS3A30	Adjustable Single	300	4
LEXDSS5T30	Adjustable Twin	500	8

Construction & Installation

	Length (mm)	Width (mm)	Height (mm)	Weight(kg)	Ingress Protection	Impact Resistance
LEXDSS5UD30	107	85	150	0.4	IP54	IK04
LEXDSS5UD30P	107	68	205	0.5	IP54	IK04
LEXDSS3F30	106	85	118	0.3	IP54	IK04
LEXDSS3A30	85	85	172	0.4	IP54	IK04
LEXDSS5T30	132	132	170	0.6	IP54	IK04

Technical Information

	Life time hours	Temperature range	Voltage Range	Frequency(hz)	Approval	Electrical Class	Power Factor
LEXDSS5UD30	30000	0°C 25°C	220V-240V	50-60	CE	1	0.5
LEXDSS5UD30P	30000	0°C 25°C	220V-240V	50-60	CE	1	0.5
LEXDSS3F30	30000	0°C 25°C	220V-240V	50-60	CE	1	0.5
LEXDSS3A30	30000	0°C 25°C	220V-240V	50-60	CE	1	0.5
LEXDSS5T30	30000	0°C 25°C	220V-240V	50-60	CE	1	0.5

GU10 Lampholder

- Decorative GU10 wall light with robust stainless steel housing
- Fixed and adjustable options including PIR
- Perfect for external domestic applications including patios, walkways and entrances

Overview

Code	Type	Lampholder	Max. Wattage Per Lamp
LEXDSSUD	-	GU10	0
LEXDSSUDPIR	-	GU10	0

Construction & Installation

	Length (mm)	Width (mm)	Height (mm)	Weight(kg)	Ingress Protection	Impact Resistance
LEXDSSUD	94	68	160	0.8	IP54	IK04
LEXDSSUDPIR	111	68	219	0.8	IP54	IK04

Technical Information

	Life time hours	Temperature range	Voltage Range	Frequency(hz)	Approval	Electrical Class	Power Factor
LEXDSSUD	-	0°C 25°C	220V-240V	50-60	CE	-	-
LEXDSSUDPIR	-	0°C 25°C	220V-240V	50-60	CE	-	-